



RESILIENT SEAT VALVE BOLT DATA

LUG BF SERIES FLANGE BOLT

DATA

LUG TYPE							
Valve Size	Holes	Thread Description	No.	Standard Stud	Machine Bolt	No.	Short Studs
2	4	5/8"-11 UNC	8	2 1/4"	1 1/2"	0	-
2.5	4	5/8"-11 UNC	8	2 1/2"	1 1/2"	0	-
3	4	5/8"-11 UNC	8	2 1/2"	1 3/4"	0	-
4	8	5/8"-11 UNC	16	2 1/2"	1 3/4"	0	-
5	8	3/4"-10 UNC	16	2 3/4"	2"	0	-
6	8	3/4"-10 UNC	16	2 3/4"	2"	0	-
8	8	3/4"-10 UNC	16	3"	2 1/4"	0	-
10	12	7/8"-9 UNC	24	3 1/4"	2 1/4"	0	-
12	12	7/8"-9 UNC	24	3 1/4"	2 1/2"	0	-
14	12	1"-8 UNC	24	3 3/4"	2 3/4"	0	-
16	16	1"-8 UNC	32	3 3/4"	3"	0	-
18	16	1 1/8"-7 UNC	32	4"	3 1/4"	0	-
20	20	1 1/8"-7 UNC	40	4"	4"	0	-
24	20	1 1/4"-7 UNC	40	4 1/4"	4 1/4"	0	-
28	28	1 1/4"-7 UNC	48	6 1/2"	5"	8	5 1/2"
30	28	1 1/4"-7 UNC	48	6 1/2"	5"	8	5 1/2"
32	28	1 1/2"-6 UNC	48	7 1/4"	5 1/2"	8	6"
36	32	1 1/2"-6 UNC	56	7 3/4"	6"	8	6 1/4"
40	36	1 1/2"-6 UNC	64	8"	6"	8	6 1/2"
42	36	1 1/2"-6 UNC	64	8"	6 1/4"	8	6 1/2"
48	44	1 1/2"-6 UNC	80	8 3/4"	7"	8	7"

 <small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PRATT INDUSTRIAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PRATT INDUSTRIAL IS PROHIBITED.</small>	No.	Revision	Date	Drawn by	Title	File No.
	0		10-3-14	AC	LUG	
				Checked by	BF SERIES FLANGE BOLT DATA	Date of Issue
				Approved by	DWG No. BD-100114-BF2	Date of Issue
						10-3-14